

# WATERWISE® DISTILLER 7000 MAINTENANCE RECORD CHART (Residential Use)

Always follow instructions in Use & Care Guide when performing maintenance procedures.



**IMPORTANT: NEVER** touch or remove boiler while Distiller is operating. Let cool at least six hours after a cycle is finished or interrupted. Boiling water or steam can cause severe burns. To avoid personal injury, unplug boiler tank cord only after “Fan” and “Power” switches are turned off, distiller is unplugged from wall outlet, and unit has completely cooled.



Date Installed	___/___/___	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
<b>Boiler Tank</b> Empty every 15-20 gallons Clean at least every week <b>(DO NOT immerse in water or other liquid)</b> After cleaning boiler, be sure tank plug is fully inserted into receptacle	YEAR	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY
	YEAR	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY
<b>Post Filter</b> Change every 2 months or every 60-80 gallons													
<b>Prefilter</b> Change every 9-12 months or every 1,000 gallons													
<b>Reservoir (inside)</b> Clean and steam sterilize every 6 months (see Use & Care Guide for details)													
<b>Condensing Coil</b> Clean fins when dust or dirt accumulates Use soft brush on vacuum cleaner													
<b>Exterior Surfaces</b> Wipe with soft, damp cloth Polish may be used on stainless steel													
<b>Boiler Tank Gasket</b> Replace as needed													
<b>Boiler Lid Knob O-Ring</b> Replace as needed													

**NOTES:** \_\_\_\_\_

# WATERWISE® DISTILLER 7000 MAINTENANCE RECORD CHART (Residential Use)

Always follow instructions in Use & Care Guide when performing maintenance procedures.



**IMPORTANT:** NEVER touch or remove boiler while Distiller is operating. Let cool at least six hours after a cycle is finished or interrupted. Boiling water or steam can cause severe burns. To avoid personal injury, unplug boiler tank cord only after “Fan” and “Power” switches are turned off, distiller is unplugged from wall outlet, and unit has completely cooled.



Date Installed	___/___/___	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
<b>Boiler Tank</b> Empty every 15-20 gallons Clean at least every week (DO NOT immerse in water or other liquid) After cleaning boiler, be sure tank plug is fully inserted into receptacle	YEAR	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY
	YEAR	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY	DAY
<b>Post Filter</b> Change every 2 months or every 60-80 gallons													
<b>Prefilter</b> Change every 9-12 months or every 1,000 gallons													
<b>Reservoir (inside)</b> Clean and steam sterilize every 6 months (see Use & Care Guide for details)													
<b>Condensing Coil</b> Clean fins when dust or dirt accumulates Use soft brush on vacuum cleaner													
<b>Exterior Surfaces</b> Wipe with soft, damp cloth Polish may be used on stainless steel													
<b>Boiler Tank Gasket</b> Replace as needed													
<b>Boiler Lid Knob O-Ring</b> Replace as needed													

**NOTES:** \_\_\_\_\_

OVER